

Waste JAMES



Ø90 Shower tray



Ø60 Shower tray



Ø50 Shower tray

horizontal

oblique

vertical

*The first
multi-directional quick
flow-rate shower waste !*



WIRQUIN

wirquin.com

PRODUCT ADVANTAGES

• A veritable revolution, the **multi-directional outlet** enables it to be adapted to all types of configurations.

An advantage for the installer : pipes can be fitted where needed since the waste adapts to the installers needs.

An advantage for the distributor : only one reference per drilling diameter to deal with.

• Thanks to its **very quick flow rate**, the James waste is just as effective in an extra-flat shower tray as in a standard one.

L/mn flow rate	under 120 mm of water			under 15 mm of water			
	diameter	Ø50	Ø60	Ø90	Ø50	Ø60	Ø90
horizontal outlet		53L/mn	53L/mn	53L/mn	30L/mn	30L/mn	30L/mn
vertical outlet		58L/mn	58L/mn	58L/mn	50L/mn	50L/mn	50L/mn

Its flow rate in $\varnothing 50$ and $\varnothing 60$ is more than twice as fast as the NF Norm requirements, which require a flow rate equal to or greater than 24L/mn.

- **The removable filter** was designed to retain hair and other waste matter. It is easy to remove and can be rinsed with water. Regular cleaning avoids risk of blockage.
- **The very compact** James waste takes up next to no space and can be fitted into most shower trays on the market.
- **The covering waste washer** was designed for easy fitting. It stays put and does not slide out of place while the shower tray is being fitted.
- **The tightening spanner**, which was specially made for the James waste, fits easily into your hand and enables to screw the grid onto the plug effortlessly.
- The same product is available in three different diameters: $\varnothing 50$, $\varnothing 60$ and $\varnothing 90$ mm.

TECHNICAL CHARACTERISTICS

• The JAMES waste can be adapted onto all standard stoneware, enamelled steel or synthetic shower trays with thicknesses of between 0 and 25 mm for $\varnothing 50$ and $\varnothing 60$ shower trays and between 3 and 25 mm for $\varnothing 90$ mm shower trays.

- Depth of seal: 50 mm
- ABS grate in chrome finish
- Guaranteed 5 years
- The resolutely European James waste is available in :



$\varnothing 40$ mm outlet (to be screwed in or glued)



$\varnothing 40$ mm English outlet (to be glued or pushed on)



$\varnothing 50$ mm outlet (to be glued or pushed on)

SALES TOOLS

Packaging :

Box in 5 colours : The box has interior wedging that keeps the components in place during transport and avoids them bumping together.



Sales concept :

The ZOOM display unit can be ordered empty (ref. 99103001) and the different diametres can be ordered seperately according to the client's requirements.

Description	Ø	Outlet	Colour	Pack.	Réf.	Bare code	PCB
JAMES 5043B	$\varnothing 50$	$\varnothing 43$	Chrome	Box	34210101	337553905917 9	01/26
JAMES 9043B	$\varnothing 90$	$\varnothing 43$	Chrome	Box	34230101	337553905916 2	01/26
JAMES 5050B	$\varnothing 50$	$\varnothing 50$	Chrome	Box	34210201	337553905919 3	01/26
JAMES 9050B	$\varnothing 90$	$\varnothing 50$	Chrome	Box	34230201	337553905918 6	01/26
JAMES 5040B	$\varnothing 50$	$\varnothing 40$	Chrome	Box	34210001	337553905306 1	04/26
JAMES 6040B	$\varnothing 60$	$\varnothing 40$	Chrome	Box	34220001	337553905307 8	04/26
JAMES 9040B	$\varnothing 90$	$\varnothing 40$	Chrome	Box	34230001	337553905308 5	04/26

WIRQUIN Plastiques - 11 rue du Château de Bel Air - 44477 Carquefou cedex FRANCE



Easy to fit with the covering washer



Easy to clean thanks to the removable filter that retains hairs



Assembly spanner supplied

